

When an Enhanced Apple //e system is cold booted, the RamFactor firmware (ROM) determines whether the card has been formatted and is bootable. If it is bootable, it will boot into the appropriate operating system. If not, the Apple ROM will continue with the slot search for the next bootable device. Apples with non-enhanced firmware will not support either the RamFactor or the Apple II Memory Expansion card as a cold-bootable device.

Whenever a PR#s command is issued or execution starts at Cs00, the RamFactor ROM again determines whether the card is bootable. If the RAMdisk is bootable the ROM will boot into the appropriate operating system. If a non-bootable RAMdisk is encountered, the ROM will enter the RamFactor Partition Manager firmware. Since an unpartitioned, bootable RamFactor RAMdisk will not allow access to the RPM firmware using the PR#s command, use the Cs10G command to force the activation of the RPM firmware. But remember, this will cause the entire contents of the RamFactor to be cleared.

Whenever the IN#s command is issued, the RamFactor ROM checks for the presence of the DOS 3.3 operating system. If DOS 3.3 is not found, the IN#s command has the same effect as the PR#s command. That is, if a bootable non-DOS 3.3 RAMdisk is present, it will boot; if not, it will access the RPM firmware. If DOS 3.3 is found, the RamFactor firmware will patch the RWTS routine, allowing access to the RAMdisk.

By activating the RamFactor Partition Manager firmware, the card is divided into nine partitions, with all of the available memory in the first partition, except for 1024 bytes which the RPM reserves for its own use. The other eight partitions are initially empty. For example, a one Megabyte RamFactor first accessed by ProDOS would yield a 1024K RAMdisk. When the Partition Manager is called, the first partition would then yield 1023K.

Once the card has been formatted into the nine partitions, access through DOS, ProDOS, or the Protocol Converter will deal with the currently selected partition. To recall the RPM menu to select another partition, use the PR#s command. The PR#s command does not boot a bootable partition.